

CV Title	CATH	Vh	lh	SCREEN		FOCUS	DEF.	VA3 Max KV	Sensitivity mm/v		BASE	DESCRIPTION	PIN CONNECTIONS											
				Col	Max Dia (mm)				X	Y			1	2	3	4	5	6	7	8	9	10	11	12
1524	IH	4.0	1.1	A	92.0	ES	ES	6.0	760	1000	SC12	For VA3 read VA4	G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1525	IH	4.0	1.1	A	70.0	ES	ES	1.5	170	170	12 Pin Spigot		C	G	H	H	A2	-	Y2	X2	A3	X1	Y1	-
1526	IH	4.0	1.1	Green	70.0	ES	ES	3.0	500	500	12 Pin Spigot	For VA3 read VA4 A4 on side	C	G	H	H	A2	-	Y2	X2	A1	X1	Y1	-
1527																								
1528	IH	4.0	1.0	A	295.0	ES	ES	7.0	1345	1300	SC12	CV1185 with special screen												
1529	IH	4.0	1.0	Blue	90.0	ES	ES	5.0	357	780	SC12		G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1530	IH	4.0	1.0	A	165.0	ES	EM	8.0	-	-	0	A3 side contact	-	A1	A2	-	G	C	H	H				
1531																								
1532																								
1533																								
1546	IH	4.0	1.0	A	306.0	EM	EM	9.0	-	-	0	A on side contact	-	H	-	-	G	-	H	C				
1547	IH	4.0	1.1	A	92.0	ES	ES	6.0	760	1040	SC12	For VA3 read VA4	G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1548																								
1549	IH	4.0	1.0	A	300.0		ES	6.5	1000	1000	SC12		C	G	H	H	-	A2	-	Y2	X2	A3	X1	Y1
1587	IH	4.0	1.0	Green	90.0		ES	5.0	357	780	SC12		G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1588	IH	4.0	1.1	Green	70.0		ES	1.0	170	170	12 Pin Spigot		C	G	H	H	A2	-	Y2	X2	A3	X1	Y1	-
1589	IH	4.0	1.0	A	300.0		ES	6.5	1000	1000	SC12		C	G	H	H	-	A2	-	Y2	X2	A3	X1	Y1
1590	IH	4.0	1.0	A	300.0		ES	6.5	1000	1000	SC12		C	G	H	H	-	A2	-	Y2	X2	A3	X1	Y1
1591	IH	4.0	1.0	A	160.0	ES	ES	6.0	720	880	SC12		G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1592	IH	4.0	1.0	A	160.0	ES	ES	6.0	720	880	SC12		G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1593	IH	4.0	1.0	A	160.0	ES	ES	6.0	720	880	SC12		G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1594	IH	4.0	1.0	A	160.0	ES	ES	6.0	720	880	SC12		G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1595	IH	4.0	1.0	A	160.0	ES	ES	6.0	720	880	SC12		G	C	H	H	A1	A2	Co	Y2	X2	A3	X1	Y1
1596	IH	4.0	1.1	Green	116.0	ES	ES	2.0	530	370	12 Pin Spigot	Split beam	C	G	H	H	-	A2	A1	Y2	X2	A3	X1	Y1