

## TRIODES

TITLE	CATH	Vh	Ih (A)	Max. Va	Ia m/a	Ia peak m/a	Max. Wa	G.m.	u	Ra	MAX Mc/s	BASE	DESCRIPTION	PIN CONNECTIONS									
														1	2	3	4	5	6	7	8	9	TC
854	IH	6.3	3.0	275	4.1	(triode section)		1.3	20			US7	Double Diode Triode	H	A	Sh	A'	A"	C	H			G
855	DH	8.5	16.8	30000	0.5	15000	300	5.8					Spec. Pulse Amplifier										
856																							
858	IH	6.3	0.45	330	9		1.6	5.5	38				B7G H.F. Twin Triode Miniature	A'	A	H	H	G	G'	C	H		
860	IH	6.3	3.0	530	1.2			1.5	70			0	High/u	-	H	A	-	-	-	H	C		G
861	IH	6.3	3.0	330	1.2			1.5	70			0	High/u, Bantam	S	H	A	-	-	-	H	C		G
862	IH	6.3	0.15	275	8			1.9	17			0	Detector Amplifier	-	H	A	-	G	-	H	C		
867	IH	6.3	0.3	275	9.5	(triode)	2.75	1.9	16			0	Double Diode Triode	Sh	G	C	A'	A"	A	H	H		
870	IH	6.3	0.3	250	6			1.0	6.3	8500		0	Double Diode Triode	-	H	A	A'	A"	-	H	C		G
872	IH	6.3	0.3	200	4.6		8					0	Double Triode	-	H	A	G	G'	A'	H	C		
879	IH	6.3	0.3	330	1			1.6	100			B8G	High/u	H	A	-	-	-	G	C	H		
882	IH	6.3	0.3	250	0.9			1.1	100	91000		B8G	Double Diode Triode High/u	H	A	G	C	A'	A"	C	H		
887	IH	6.3	0.2	300	1.35			1.0	100			B8G	Double Diode Triode High/u	H	A	G	C	A'	A"	C	H		
891	IH	6.3	0.3	275	9.5	(triode)	2.75	1.9	16			B8G	Double Diode Triode	H	A	G	C	A'	A"	C	H		
893	IH	6.3	0.3	275	2.3		1.1	1.6	70			B8G	Double Diode Triode	H	A	G	C	A'	A"	C	H		
896	IH	6.3	0.3	275	2.3			1.6	70	44000		0	Double Diode Triode High/u	H	C	A	G	A'	A"	C'	H		
898	IH	6.3	0.6	330	9.4		2.75	2.6	20			B8G	Double Triode	H	C	A	G	G'	A'	C'	H		
906	DH	7.5	1.25	425			12	1.6	8	5000		BC4	(Non microphonic)	F	A	G	F						
919	IH	12.6	0.15	330	1			1.6	100	0.2M		0	High/u	Sh	C	G	-	A	-	H	H		
920	IH	12.6	0.15	330	1			1.6	100	0.2M		0	G.T. Version of 919	-	C	G	-	A	-	H	H		
924	IH	12.6	0.15	275	2.3		1.1	1.6	70	0.2M		0	Double Triode	G	A	C	G'	A'	C'	H	H		
925	IH	12.6	0.3	330	9		2.75	3.0	20	10000		0	Double Triode	G	A	C	G'	A'	C'	H	H		
930	IH	12.6	0.15	275	2.3		1.1	1.6	70	0.2M		L.I.	Double Triode	H	C	A	G	G'	A'	C'	H		